





OPEN TYPE BLIND RIVET

Body: **ALUMINIUM(5052)**

Mandrel: **Steel**

Head: **Dome**




Code	Diameter(d) X Length(L) (mm)	Head Diameter (Ave) (dk) (mm)	Head Thickness (Max) (K) (mm)	Hole Size (mm)	Grip Range  (mm)	Tensile Strength  (N)	Shear Strength  (N)
AS	2.4 x 06	4.75	0.90	2.5	1.50—3.50	360	320
	2.4 x 08				3.50—6.00		
AS	3.2 x 06	6.35	1.20	3.3	0.80—3.50	670	540
	3.2 x 08				2.50—5.50		
	3.2 x 10				4.50—7.50		
	3.2 x 12				6.50—9.50		
	3.2 x 15				9.50—12.50		
	3.2 x 18				12.50—15.50		
	3.2 x 21				15.50—18.50		
	3.2 x 24				18.50—21.50		
AS	4.0 x 06	7.95	1.40	4.1	1.00—3.00	1030	850
	4.0 x 08				2.00—5.00		
	4.0 x 10				4.00—7.00		
	4.0 x 12				6.00—9.00		
	4.0 x 15				9.00—12.00		
	4.0 x 18				12.00—15.00		
	4.0 x 21				15.00—18.00		
	4.0 x 24				18.00—21.00		
AS	4.8 x 06	9.50	1.60	4.9	1.20—2.50	1430	1160
	4.8 x 08				2.00—4.50		
	4.8 x 10				3.50—6.50		
	4.8 x 12				5.50—8.50		
	4.8 x 15				8.50—11.50		
	4.8 x 18				11.50—14.50		
	4.8 x 21				14.50—17.50		
	4.8 x 24				17.50—20.50		
	4.8 x 27				20.51—23.50		
	4.8 x 30				23.51—26.50		
	4.8 x 35				26.50—31.50		
	4.8 x 40				31.50—36.50		
AS	6.4 x 12	12.70	2.10	6.5	4.50—7.50	2490	2050
	6.4 x 15				7.50—10.50		
	6.4 x 18				10.50—13.50		
	6.4 x 21				13.50—16.50		
	6.4 x 24				16.50—19.50		
	6.4 x 27				19.50—22.50		
	6.4 x 30				22.50—25.50		


OPEN TYPE BLIND RIVET

Body: ALUMINIUM(5052)

Mandrel: Steel

Head: Countersunk




Code	Diameter(d) X Length(L) (mm)	Head Diameter (Ave) (dk) (mm)	Hole Size (mm)	Grip Range  (mm)	Tensile Strength (N)	Shear Strength (N)
ASC	3.2 x 06	5.60	3.3	0.80—3.50	670	540
	3.2 x 08			2.50—5.50		
	3.2 x 10			4.50—7.50		
	3.2 x 12			6.50—9.50		
ASC	4.0 x 08	7.15	4.1	2.00—5.00	1030	850
	4.0 x 10			4.00—7.00		
	4.0 x 12			6.00—9.00		
	4.0 x 15			9.00—12.00		
ASC	4.8 x 10	8.85	4.9	3.50—6.50	1430	1160
	4.8 x 12			5.50—8.50		
	4.8 x 15			8.50—11.50		
	4.8 x 18			11.50—14.50		
	4.8 x 21			14.50—17.50		
	4.8 x 24			17.50—20.50		
	4.8 x 30			23.50—26.50		
ASC	6.4 x 12	12.03	6.5	4.50—7.50	2490	2050
	6.4 x 15			7.50—10.50		
	6.4 x 18			10.50—13.50		




OPEN TYPE BLIND RIVET

Body: **ALUMINIUM(5052)**

Mandrel: Steel

Head: Large Flange



Code	Diameter(d) X Length(L) (mm)	Head Diameter (Ave) (dk) (mm)	Head Thickness (Max) (K) (mm)	Hole Size (mm)	Grip Range  (mm)	Tensile Strength  (N)	Shear Strength  (N)
ASL	3.2 x 08	9.50	1.70	3.3	2.50—5.50	670	540
	3.2 x 10				4.50—7.50		
	3.2 x 12				6.50—9.50		
ASL	4.0 x 10	11.90	2.00	4.1	4.00—7.00	1030	850
	4.0 x 12				6.00—9.00		
	4.0 x 15				9.00—12.00		
ASL	4.8 x 10	15.85	2.40	4.9	3.50—6.50	1430	1160
	4.8 x 12				5.50—8.50		
	4.8 x 15				8.50—11.50		
	4.8 x 18				11.50—14.50		
	4.8 x 21				14.50—17.50		
	4.8 x 24				17.50—20.50		
	4.8 x 27				20.51—23.50		
	4.8 x 30				23.51—26.50		


Use when the head is in direct contact with a soft material, eg plastic, wood, fiberglass.

OPEN TYPE BLIND RIVET

Body: **STEEL**

Mandrel: Steel

Head: Dome




Code	Diameter(d) X Length(L) (mm)	Head Diameter (Ave) (dk) (mm)	Head Thickness (Max) (K) (mm)	Hole Size (mm)	Grip Range (mm)	Tensile Strength (N)	Shear Strength (N)
SS	3.2 x 06	6.35	1.20	3.3	0.80—3.50	1380	1160
	3.2 x 08				2.50—5.50		
	3.2 x 10				4.50—7.50		
	3.2 x 12				6.50—9.50		
	3.2 x 15				9.50—12.50		
SS	4.0 x 06	7.95	1.40	4.1	1.00—3.00	2090	1650
	4.0 x 08				2.00—5.00		
	4.0 x 10				4.00—7.00		
	4.0 x 12				6.00—9.00		
	4.0 x 15				9.00—12.00		
	4.0 x 21				15.00—18.00		
SS	4.8 x 08	9.50	1.60	4.9	2.00—4.50	3030	2400
	4.8 x 10				3.50—6.50		
	4.8 x 12				5.50—8.50		
	4.8 x 15				8.50—11.50		
	4.8 x 18				11.50—14.50		
	4.8 x 21				14.50—17.50		
	4.8 x 27				20.51—23.50		
SS	6.4 x 12	12.70	2.10	6.5	4.50—7.50	5520	4450
	6.4 x 15				7.50—10.50		
	6.4 x 18				10.50—13.50		
	6.4 x 21				13.50—16.50		


OPEN TYPE BLIND RIVET

Body: **STAINLESS STEEL (304)**

Mandrel: Steel

Head: **Dome**
(Half Stainless Steel)





Code	Diameter(d) X Length(L) (mm)	Head Diameter (Ave) (dk) (mm)	Head Thickness (Max) (K) (mm)	Hole Size (mm)	Grip Range  (mm)	Tensile Strength (N)	Shear Strength (N)
STS	3.2 x 06	6.35	1.20	3.3	0.80—3.50	2593	1870
	3.2 x 08				2.50—5.50		
	3.2 x 10				4.50—7.50		
	3.2 x 12				6.50—9.50		
	3.2 x 15				9.50—12.50		
STS	4.0 x 08	7.95	1.40	4.1	2.00—5.00	4012	2893
	4.0 x 10				4.00—7.00		
	4.0 x 12				6.00—9.00		
	4.0 x 15				9.00—12.00		
STS	4.8 x 08	9.50	1.60	4.9	2.00—4.50	5872	4228
	4.8 x 10				3.50—6.50		
	4.8 x 12				5.50—8.50		
	4.8 x 15				8.50—11.50		
	4.8 x 18				11.50—14.50		
	4.8 x 21				14.50—17.50		

Body: **STAINLESS STEEL (304)**

Mandrel: Steel

Head: **Countersunk**
(Half Stainless Steel)



Code	Diameter(d) X Length(L) (mm)	Head Diameter (Ave) (dk) (mm)	Hole Size (mm)	Grip Range  (mm)	Tensile Strength (N)	Shear Strength (N)
STSC	4.8 x 10	9.50	4.9	3.50—6.50	5872	4228
	4.8 x 15			8.50—11.50		


OPEN TYPE BLIND RIVET




Body: **STAINLESS STEEL (304)**

Mandrel: Stainless Steel

Head: **Dome**

(Full Stainless Steel)




Code	Diameter(d) X Length(L) (mm)	Head Diameter (Ave) (dk) (mm)	Head Thickness (Max) (K) (mm)	Hole Size (mm)	Grip Range  (mm)	Tensile Strength  (N)	Shear Strength  (N)
STST	3.2 x 06	6.35	1.20	3.3	0.80—3.50	2593	1870
	3.2 x 08				2.50—5.50		
	3.2 x 10				4.50—7.50		
	3.2 x 15				9.50—12.50		
STST	4.0 x 08	7.95	1.40	4.1	2.00—5.00	4012	2893
	4.0 x 10				4.00—7.00		
	4.0 x 12				6.00—9.00		
	4.0 x 15				9.00—12.00		
STST	4.8 x 08	9.50	1.60	4.9	2.00—4.50	5872	4228
	4.8 x 10				3.50—6.50		
	4.8 x 12				5.50—8.50		
	4.8 x 15				8.50—11.50		
	4.8 x 18				11.50—14.50		
	4.8 x 21				14.50—17.50		
	4.8 x 24				18.00—20.00		
STST	6.4 x 15	12.70	2.10	6.5	7.50—10.50	9350	7570
	6.4 x 25				16.50—19.50		




Body: **STAINLESS STEEL (304)**

Mandrel: Stainless Steel

Head: **Countersunk**

(Full Stainless Steel)



Code	Diameter(d) X Length(L) (mm)	Head Diameter (AVE) (dk) (mm)	Hole Size (mm)	Grip Range  (mm)	Tensile Strength  (N)	Shear Strength  (N)
STSTC	4.8 x 10	9.50	4.9	3.50—6.50	5872	4228
	4.8 x 15			8.50—11.50		

OPEN TYPE BLIND RIVET

Body:


NICKEL COPPER (Monel)




Mandrel:

Steel

Head:

Dome



Code	Diameter(d) X Length(L) (mm)	Head Diameter (AVE) (dk) (mm)	Head Thickness (MAX) (K) (mm)	Hole Size (mm)	Grip Range  (mm)	Tensile Strength  (N)	Shear Strength  (N)
MP	3.2 x 10	6.00	0.89	3.3	4.50—7.10	1900	1500
MP	4.8 x 10	8.12	1.30	4.9	3.50—6.10	3750	3300
	4.8 x 12				5.50—8.50		
	4.8 x 16				8.50—12.00		
	4.8 x 19				12.00—15.00		
MP	6.4 x 12	10.82	1.65	6.5	4.50—7.50	6750	5400
	6.4 x 18				10.50—13.00		

Body:


NICKEL COPPER (Monel)




Mandrel:

Steel

Head:

Countersunk



Code	Diameter(d) X Length(L) (mm)	Head Diameter (AVE) (dk) (mm)	Hole Size (mm)	Grip Range  (mm)	Tensile Strength  (N)	Shear Strength  (N)
MPC	4.8 x 10	8.12	4.9	3.50—5.80	3750	3300
	4.8 x 12			5.50—7.00		
	4.8 x 16			8.50—11.00		
	4.8 x 19			12.00—14.20		
MPC	6.4 x 12	10.82	6.5	5.50—7.00	6750	5400
	6.4 x 18			10.50—12.50		

Suitable in very corrosive areas.
Compatible with all metals.